



## TECHNICAL PRODUCT INFORMATION

<p><b>PRODUCT TYPE</b></p>	<p align="center"><b>SWARCO PREFORMED THERMOPLASTIC</b></p> <p align="center"><b>WHITE &amp; YELLOW &amp; BLACK</b></p>						
<p><b>DESCRIPTION</b></p>	<p>Thermoplastic road marking material pre-melted and formed into lines and legends in 90 and 125 mil thickness</p>						
<p><b>FUNCTION</b></p>	<p>Provides a durable marking without the need of special thermoplastic application equipment and know-how.</p>						
<p><b>SPECIFICATIONS</b></p>	<table border="0"> <tr> <td>ASTM D 4592</td> <td>ASTM E 303</td> <td>ASTM E 1710</td> </tr> <tr> <td>ASTM D 6628</td> <td>AASHTO M249</td> <td>AASHTO T-250</td> </tr> </table>	ASTM D 4592	ASTM E 303	ASTM E 1710	ASTM D 6628	AASHTO M249	AASHTO T-250
ASTM D 4592	ASTM E 303	ASTM E 1710					
ASTM D 6628	AASHTO M249	AASHTO T-250					
<p><b>TECHNICAL DATA</b></p> <p>Reflectivity</p> <p>Color Coordinates ASTM D 6628</p> <p>Skid Resistance ASTM E 303</p> <p>Application Conditions</p> <p>Application Temperature</p> <p>Storage</p> <p>Shelf Life</p>	<p>Initial: White 400 min mcd/sq. ft. /lux. Yellow 250 min mcd/sq. ft./lux Black &lt; 5 min mcd/sq. ft./lux</p> <p>Due to the nature of the installation method, installed retro values can vary from one installer to another. Swarco will work directly with the installer to assure that the customer's reflectivity requirements are met.</p> <p>Our pavement marking materials are specifically created with Color in mind. They have been manufactured to conform to standard traffic marking Color requirements.</p> <p>Minimum Initial <math>\geq 45</math></p> <p>Proper surface preparation is essential to obtaining consistent adhesion of the road marking tape. The surface must be free of moisture, loose or caked dirt, gravel, oily residues, salt residues or other foreign materials. Thoroughly read application instructions prior to use or contact your Swarco sales representative.</p> <p>The minimum recommended application temperature is 32° F (0° C) for the air and the roadway surface, with both temperatures rising, no pre-heating of the surface is necessary, except that required for surface moisture removal. The markings are best applied when night-time temperatures remain above freezing. Do not install on roadways which have had rainfall within 24 hours prior to application.</p> <p>Storage: Markings should be stored indoors at temperatures between 50° F (15° C) and 100° F (38° C)</p> <p>Shelf Life: 24 months from receipt of material in original packaging.</p>						
<p><b>CONTACT INFORMATION</b></p>	<p align="center"><b>SWARCO</b></p> <p align="center">P.O. Box 89, Columbia, TN 38401 Phone: 800-216-8781, Fax: 931-388-4039</p>						

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable but the accuracy and completeness thereof is not guaranteed. Data is subject to alteration due to technical advances.