

SWARCO REPAIR FLAKES

TECHNICAL INFORMATION

PRODUCT DESCRIPTION

Thermoplastic granules for the repair of damaged areas in asphalt surfaces by filling joints and cracks.

SWARCO Repair Flakes are easy to apply and harden within a few minutes, allowing the repaired area to be reopened to traffic quickly.

APPLICATION & PROCESSING

Suitable for all types of asphalt surfaces. Concrete or cement-bound surfaces require prior priming (for example, when used as a joint filler on paving substrates). The area to be repaired must be clean, dry, and free from dust and grease. In cold or wet conditions, the substrate must be thoroughly preheated or dried. Where necessary, apply a suitable primer and allow it to flash off before use.

SWARCO Repair Flakes are spread into the area to be repaired until the material stands slightly above the surface level. The flakes are then heated with a hand torch until the molten material settles into the joints and cracks. For joint and crack depths greater than 5 mm, the material must be applied in several layers.

PRODUCT INFORMATION

Appearance	Granulate
Specific density	1,90 g/cm ³ – 2,10 g/cm ³
Melting point	85°C to 120°C
Flash point	> 240°C
Colour	Grey, shade may vary slightly
Coating	The flakes are coated to prevent agglomeration during transport and storage
Trafficability	A few minutes after application
Storage stability	12 months in unopened packaging and protected from direct UV exposure; after opening, store in a dust-free environment
Packaging	15 kg, paper bags
Labelling	Not subject to labelling under GGVS and VBF
Health & Safety	Please read the Safety Data Sheet before use

The information given in this document is based on our best knowledge and experience. We reserve the right to make changes in the course of technical development.