

# **SWARCOBLAST Glass Blasting Beads**

# **Technical Information**

## MAIN CHARACTERISTICS & FIELD OF APPLICATION

SWARCOBLAST glass blasting beads are a non-metallic mineral fine blasting medium made of glass. The blasting beads are suitable for gentle cleaning, deburring, smoothing, matting, solidifying surfaces and reduction of surface roughness of metallic and austenitic materials.

#### **AVAILABLE GRAIN SIZES**

Sieving Range	μm	1-50 40-70 50-105 70-110 90-150 100-200	200-300 200-400 300-400 400-600 400-800 600-800

Further customized particle-size distributions are possible upon request.

#### **MATERIAL**

**Chemical composition** SWARCOBLAST glass blasting beads are melted from soda lime glass. Chemical Composition according to DIN 8201:

$SiO_2$	68,0-75,0 %
$Al_2O_3$	0-2,5 %
MgO	0-5,0 %
CaO	7,0-12,0 %
Na <sub>2</sub> O	12,0-18,0 %
Other	max. 2,0 %

For technical production reasons, foreign impurities, additives and oversized grains up to max. 0.1 wt% can occur. Dust content or undersized particles (unless otherwise stated in the sieve curve) are possible up to 0.5 wt%.

# PRODUCT INFORMATION

Refractive index ≥ 1,5

Roundness > 80 %

Processing pressure of glass blasting beads should not exceed 4 bar.



#### **SPECIFICATIONS**

Test or sieving specifications according to defined factory specifications.

## **PACKAGING & STORAGE**

Packaging in 25 kg paper bags with poly-inner bag, packaging in 1000 kg big bags is possible upon request.

Protect product against humidity. Dry and sheltered storage.

#### IMPORTANT INFORMATION

Please consider our General Terms and Conditions and the general notes of the Technical Information Sheet. No liability is accepted for any errors. The information is provided to our best knowledge and experience. This information is, however, no warranty for any properties of the material. We provide this information without obligation, also regarding the rights of third parties. The users have to make sure that the material is appropriate for the respective application.