



CLASSIFICATION LOOP DETECTOR MC3224SL



VEHICLE CLASSIFICATION WITH SINGLE LOOPS

SWARCO TRAFFIC SYSTEMS GMBH is a member of the internationally active SWARCO group, the one-stop shop for road markings, signage, signalisation and traffic management – your reliable partner for traffic solutions.

The MC2224SL loop detector was specifically designed for vehicle detection with classification by means of single loops for traffic data acquisition and traffic control. The detector is designed for DIN-rail mount and includes a complete overvoltage protection module for the inductive loops.

The single loop detector is not suited for speed and length measurement or detection of driving direction and wrong way drivers. Inherent to its functional principle, the excellent classification accuracy of the double-loop variants is reduced with the SL version.

FEATURES:

- Acquisition of traffic data in accordance with TLS¹/BAST² for 4 lanes with single loops, occupancy rate in connection with a controller
- Serial data transfer via interface
- 4 Open collector switching outputs for detection signals or optional functions
- Maintenance-free
- Low power consumption
- Highly-reliable data acquisition, absolutely independent of climatic conditions and insensitive to interferences
- Automatic alignment, regulation of temperature fluctuations and non-volatile storage of all operating data
- Easy and space-saving integration due to DIN rail mounting
- TBUS system: bus system integrated in DIN rail for power supply, RS485 interface and detector synchronization
- Complete integrated overvoltage protection for inductive loops, no additional components necessary

1 TLS: Technical delivery terms for roadway stations
 2 BAST: German federal highway research institute



CLASSIFICATION LOOP DETECTOR MC3224SL

FUNCTIONAL DESCRIPTION:

The MC2224SL now offers the functions and outstanding features of the SWARCO TRAFFIC SYSTEMS classification detectors in 19" plug in technology also in a DIN rail mount version. Based on the proven and tested MC2224 and the certified CD9054, it includes a complete overvoltage protection module. This integration minimizes the wiring effort and significantly reduces the required space.

The MC2224SL classifies the vehicles in (8+1) classes acc. to TLS. When TLS loops are used, the classification meets the accuracies required by the German federal highway research institute and is not influenced by e.g. weather conditions. The vehicle type is determined by means of passing-curves which have characteristic features depending on the different classes and the loop types used.

Via RS232 service interface and RS485 data interface, the detector provides the following data:

Single vehicle data:	vehicle class, time of occupancy, time gap
(8+1) classes acc. to TLS:	other vehicles / motorbike / car / van / car with trailer / HGV / HGV with trailer / HGV articulated / bus

Via the RS485 bus single-vehicle data is transferred to a controller, which takes over further data aggregation acc. to TLS-specifications. The detector automatically adjusts itself to the attached loop/feed-cable combination. Variations in temperature have no influence on data acquisition. The measuring systems are permanently checked for short or open loops, only when a definite malfunction is detected, systems are put into a failure condition. Short measuring intervals and a new procedure for speed measurement provide for the high accuracy of the measured data and the high detection speed, according to the requirements of the German federal highway research institute.

TECHNICAL DATA:

Supply voltage	nominal 24 V DC, range 10 V DC - 38 V DC
Power consumption	max. 29 mA / 0.70 W with 24 V DC
Interfaces	RS485 data interface, service interface at front (USB adapter type <i>KA-SERVICE_AJ</i> optionally available)
Switching outputs	switching output per channel: Open Collector
Dimensions	DIN rail enclosure; height: 99 mm, length: 114,5 mm, width: 22,5 mm
Operating / storage temperature	-25°C to +80°C / -40°C to +80°C
Protection	III (low voltage < 60 V DC)
Design	DIN rail mounting (TS35 EN50022), to be installed in housing or cabinet with IP54 necessary (pollution degree 2)
Terminal strip	- MSTBT 2.5/4 (top and bottom) - TBUS system 1.5/5 (back side) - functional grounding via integrated contact and DIN rail

For detailed information about the function, operation and pin assignment as well as further technical data see user manual.



SWARCO TRAFFIC SYSTEMS GMBH

SWARCO TRAFFIC SYSTEMS GMBH is one of the leading suppliers of intelligent traffic systems in Germany. Building on many decades of experience, it offers a wide range of innovative solutions for urban and interurban traffic management, including parking and traffic detection. Its nationwide service and maintenance network guarantees highest possible system availability and improved road safety. With economical, sustainable, and environmentally friendly technologies we help ensure smooth and safe traffic flows.