



## 0670 SERIES

### AthletiCoat RTU Field Marking Paint

AthletiCoat RTU is a quality, ready-to-use field marking paint designed for outdoor athletic sports fields. The VOC-free formula is safe to use on grass and dirt infields. It is designed to be used directly out of the bucket.

#### FEATURES AND BENEFITS

- Good Brightness
- VOC Free
- A more economical choice
- Safe to use on natural grass and dirt fields
- May be applied by spray, roller or brush
- Easy cleanup

#### TECHNICAL DATA

Gloss/Sheen (85°)	< 5 (Flat/Matte)
VOC Content (g/L)	0
Viscosity (Krebs Units)	93 (±3)
Density (lbs./gal)	11.4 (±0.3)
Weight Solids	44%
Volume Solids	24%
Coverage (undiluted, 1.5 mil dry film, ft <sup>2</sup> /gal)	250



#### AVAILABLE COLORS

- White
- Custom colors available upon request (minimum orders may apply)

#### PACKAGING

- 5 Gallon Containers

## 0670 SERIES

### AthletiCoat RTU Field Marking Paint

#### **SURFACE PREPARATION**

For best results, surface should be dry or have negligible moisture present.

#### **APPLICATION**

- For best results, apply when temperatures are between 40°F and 100°F.
- Apply with spray or roller equipment.
- Do not leave water or water mixed with non-subsiding cleaner for more than 24 hours in spray equipment. It is recommended to use a mixture of glycol solution and water when storing spray equipment longer than 72 hours.

#### **DILUTING**

Diluting is not recommended.

#### **INTENDED USE**

This product is designed as a temporary marking for grass, dirt or artificial turf athletic fields. May also be used as a temporary marking for parade routes, and is easily removed with pressure washing. It is not designed as a permanent marking, and should therefore not be used as a permanent marking on tennis courts, asphalt or concrete.

#### **MIXING**

Stir well before using.

#### **ENVIRONMENTAL**

- Dry paint chips are non-toxic
- VOC-Free formula will not damage turf

#### **CLEANUP**

Clean all equipment with warm, soapy water.

#### **SAFETY PRECAUTIONS**

Keep material and buckets out of reach of children. Do not intentionally inhale mist or paint vapors.

#### **SHELF LIFE**

Best used within 3 months of manufacturing date. Extra mixing may be required for material that has not been used within this time frame.

#### **STORAGE**

Store undiluted material in the original, tightly sealed container in a cool, dry place.

#### **WARRANTY**

Colorado Paint warrants to the purchaser, for six months from the date of manufacturing, that this product shall be manufactured without defects when applied according to Colorado Paint Application Instructions. This limited warranty covers material replacement only. Excluded from coverage is labor, any damage to the application surfaces or any failure of the coating caused other than by defects in the material.