

Director 60 - HPT

PERMANENT PAVEMENT MARKING TAPE WHITE & YELLOW



PRODUCT DESCRIPTION

High Performance Permanent Long-life Road Marking Tape providing exceptional reflective guidance over the life of the product.

Used for long-life lane delineation to provide superior reflectivity that will improve motorist guidance for the life of the product.

PRODUCT SPECIFICATIONS

ASTM D 4505 ASTM E 303 ASTM D 6628 ASTM E 1710

PHYSICAL PROPERTIES

- **Retroreflection – ASTM E 1710**

mcd/m2/lux	Initial
White	500
Yellow	350

- **Color - ASTM D 6628**

Our pavement marking materials are specifically created with color in mind. They have been manufactured to conform to standard traffic marking color requirements.

- **Skid resistance - ASTM E 303**

Minimum Initial BPN ≥ 45.

- **Application condition**

Proper surface preparation is essential to obtaining consistent adhesion of the permanent tape. The surface must be free of loose or caked dirt, gravel, oily residues, salt residues or other foreign material. Thoroughly read application instructions prior to use or contact your SWARCO sales representative.

- **Application temperature**

The recommended application temperature is 50°F (10°C) for the air and the roadway surface, with both temperatures rising. The markings are best applied when nighttime temperatures remain above freezing. Do not install on roadways that have had rainfall within 24 hours prior to application.

- **Prime Sealer**

DPE-4

STORAGE

Markings should be stored indoors at a minimum temperature of 60°F (15°C). Use within one year of receipt.

All statements, technical information and recommendations contained herein are based on tests we believe to be reliable but the accuracy and completeness thereof is not guaranteed. Data is subject to alteration due to technical advances.

Above information not to be taken as a warranty or representation for which we assume legal responsibility. It is offered solely for consideration, investigation and verification.

If you have any questions about proper application techniques or other technical support issues, please contact your SWARCO sales or customer service representative.

Form SI-603 Effective 9/19/2022